PROZESSTECHNIK KOMPONENTEN



SEARCH TERM INDEX - PF-SYSTEM

| | ITEM DESCRIPTION | CHAPTER | Page |
|---|---|---------|------|
| ٨ | | | |
| Α | | | |
| | Adaptor with GL thread | 2 | 8 |
| | Adaptor with hose connection | 2 | 7 |
| | Adaptor with KAMLOK connection | 2 | 10 |
| | | 2 | 11 |
| | Adaptor with milk pipe thread | | |
| | Adaptor with threaded media connection, stainless steel | 2 | 12 |
| | Adaptor with TriClamp-PTFE connection | 2 | 9 |
| | Adjustable overflow valves | 4 | 24 |
| В | | | |
| | | | |
| | Backing flanges, cast, DN 400 to DN 600 | 3 | 13 |
| | Backing flanges, glass–ANSI | 3 | 16 |
| | Backing flanges, glass-glass, plastic | 3 | 12 |
| | Backing flanges, glass-glass, stainless steel | 3 | 14 |
| | Backing flanges, glass–EN | 3 | 15 |
| | Backing flanges, undrilled, stainless steel | 3 | 17 |
| | | | |
| | Ball check valves, horizontal/vertical VNH/VNEH | 4 | 17 |
| | Ball check valves, vertical VNV | 4 | 16 |
| | Ball valves with hand lever | 4 | 19 |
| | Ball valves with pneumatic actuator | 4 | 20 |
| | Bellows for flange connection, glass-ANSI | 2 | 5 |
| | | | |
| | Bellows for flange connection, glass-EN | 2 | 4 |
| | Bellows for flange connection, glass-glass | 2 | 3 |
| | Bellows/compensators for media connection in accordance with EN 1092 | 2 | 6 |
| | Bends | 1 | 10 |
| | Blind flanges | 1 | 17 |
| | Bottom outlet valves | 4 | 22 |
| | Bush inserts | 9 | 9 |
| | | | |
| C | | | |
| | Castors for apparatus structures | 9 | 7 |
| | | - | |
| | Check valves, ball, vertical type VNV | 4 | 16 |
| | Check valves, ball, horizontal/vertical type VNH/VNEH | 4 | 17 |
| | Check valves, flange insert design | 4 | 18 |
| | Compression springs | 3 | 22 |
| | Connection flange couplings, glass-ANSI | 3 | 10 |
| | Connection flange couplings, glass-EN | 3 | 9 |
| | Connection flange couplings, glass-glass | 3 | 8 |
| | | | |
| | Connection flange couplings, glass-undrilled flange | 3 | 11 |
| | Control valves, manual | 4 | 12 |
| | Control valves, with pneumatic actuator | 4 | 13 |
| | Couplings, glass-glass, cast, DN 400 to DN 600 | 3 | 5 |
| | Couplings, glass-glass, plastic | 3 | 4 |
| | | | 7 |
| | Couplings, glass-glass, PF- to KF | 3 | |
| | Couplings, glass-glass, stainless steel | 3 | 6 |
| D | | | |
| | Davida valvas | | 0 |
| | Double valves | 4 | 9 |
| | Drain valves, on/off | 4 | 6 |
| F | | | |
| | - | | 24 |
| | Flaps | 4 | 21 |
| G | | | |
| | | | |
| | Gaskets, flat | 3 | 31 |
| | Gaskets, flat, for repeated opening and closing | 3 | 32 |
| | Gaskets, flat, with steel core | 3 | 30 |
| | Gaskets, flexible | 3 | 27 |
| | | | |
| | Gaskets, glass-glass, ring, with collar | 3 | 25 |
| | Gaskets, GMP conform | 3 | 26 |
| | Gaskets, transition, glass-enamel | 3 | 29 |
| | Gaskets, universal, KF to PF flanges | 3 | 28 |
| | Gas mixing valves | 4 | 24 |
| | Glass-fibre based tape insert | 3 | 21 |
| | a man and a | • | |

PROZESSTECHNIK KOMPONENTEN



SEARCH TERM INDEX - PF-SYSTEM

| | ITEM DESCRIPTION | CHAPTER | Page |
|-----|--|----------|----------|
| | | | |
| Н | | | |
| | High Pressure valves | 4 | 10 |
| | Hoses, product | 1 | 18 |
| | Hoses, media | 1 | 19 |
| | | | |
| | | | 40 |
| | Inserts for backing flanges Inserts, rubber/aramid fibre | 3 | 18 20 |
| | moorts, rubber/aramia hbre | <u> </u> | |
| L | | | |
| | Lifting lugs | 9 | 15 |
| | Lower support rings | 9 | 12 |
| • | | | |
| M | | | |
| | Media hoses | 1 | 19 |
| | Membrane valves | 4 | 24 |
| Р | | | |
| Г | | | |
| | Pipe sections | 1 | 3 |
| | Pipe clamps | 9 | 9 |
| | Pipe supports Pressure relief valves | 9 | 10 11 |
| | Product hoses | 4 1 | 18 |
| | | | |
| Q | | | |
| | Quick release couplings | 3 | 33 |
| | J | | |
| R | | | |
| | Rapid closures | 3 | 35 |
| | Reducers | 1 | 7 |
| | Reducing sleeves as bolt connection accessory | 3 | 23 |
| | Reducing sleeves for flanges connection ANSI | 3 | 23 |
| S | | | |
| | 0.11 | • | |
| | Saddle supports Sampling valves | 9 4 | 14 14 |
| | Sampling valves for condensable gases and collecting flasks | 4 | 15 |
| | Screw caps | 3 | 34 |
| | Spacers Splash guard for backing flange coupling, glass-glass | 1 | 5 |
| | Splash guard for backing flange coupling, glass-glass Straight through valves, on/off | 3 4 | 24 4 |
| | Straight through valves, on/off, pneumatic | 4 | 5 |
| | Structure fittings | 9 | 6 |
| | Structure tubings Support brackets | 9 | 5 11 |
| | Support rings for spherical vessel | 9 | 13 |
| T | | | |
| | | | |
| | T pieces | 1 | 13 |
| | Three way valves | 4 | 8 |
| | Transition insert PF flange to EN backing flange | 3 | 19 |
| U | | | |
| O . | | | |
| | U bends | 1 | 12 |
| | U bends with outlet | 1 | 10 |

PROZESSTECHNIK KOMPONENTEN



SEARCH TERM INDEX - PF-SYSTEM

| | ITEM DESCRIPTION | CHAPTER | PAGE |
|---|------------------|---------|------|
| V | | | |
| | | | |
| | Vent valves | 4 | 7 |
| | Vessel holders | 9 | 13 |
| X | | | |
| | X pieces | 1 | 13 |
| | | | |
| Υ | | | |
| | | | |
| | Y pieces | 1 | 16 |